KUNARK HITECH MACHINING & SALES PVT.LTD.



Kunark House, 269, Kunark Marg, Kaman Bhiwandi Road, Kaman, Vasai Road (East),Dist: Thane -401208, Maharashtra,India. Mobile:(+91) 9867973046 Factory:0250-6454895

Email: info@jkgears.com,dalbirbright@gmail.com website: www.jkgears.com



















Machine Id	:-	984	Serial No	:-	
Category	:-	Thread / Worm Grinders	Model	:-	37 type 4
Country	:-		Make	:-	Matrix
Type of Machine	:-	Thread Grinder Machine	Year	:-	0
Weight	:-	0.0	Dimensions	:-	
Power	:-		Location	:-	

Specification :-

No. 37 & 47 Universal Thread Grinding Machines

Three models are available, each having design characteristics sutaible for specific applications.

Type 1. Plain thread grinding machine : Equally sutaible for production work, toolroom work or external gauges manufacture to most international screw thread standard.

Type 2. Semi -Automatic pluge cut machines:primarily used for accurate high-speed production of short lenghths of external threads using the plunge grinding technique.

Type 3. Taper thread grinding machines: Developed from the type 1 machines for girnding precision taper screw gauges up to 1 in 4 on daimeter to API and other international standards either external or internal.

Specification:

No.37 Machine

No. 47 Machine

Maximum diameter admitted	355mm 14in		
Maximum langth batwaan controp	500mm 20in		

Maximum length between centres Maximum length ground at one setting Maximum helix angle 500mm 20in 457mm 18in 45° right or left hand

1066mm 42in 1016mm 40in

Pitch range	0,4 to 300mm 60tpi to 12in lead		
Workhead and tailstock centres	no. 4 morse		
Workhead speeds (forward)	0.21 to 31 rpm		
Workhead speeds (reverse)	6,35:25 or 100 rpm		
Wheelhead motor for grinding and c	lressing 4,5/2.25kw 6/3 hp		
Wheelhead motor for crushing	0.25 kw 1/3 hp		

Special large swign machne available 406mm (16in)