

# KUNARK HITECH MACHINING & SALES PVT.LTD.



Kunark House, 269, Kunark Marg, Kaman Bhiwandi Road, Kaman,

Vasai Road (East), Dist: Thane -401208, Maharashtra, India.

Mobile&Whatsapp: +91 9867973046, Mobile 2:- +91 7977043901

Goggle Map:- <https://maps.google.com/maps?q=19.372000+72.902095>



Email: [info@jkgears.com](mailto:info@jkgears.com), [dalbirbright@gmail.com](mailto:dalbirbright@gmail.com) website: [www.jkgears.com](http://www.jkgears.com)







Video :-

<a href="#">please click here for video no. 01</a>	
<a href="#">please click here for video no. 02</a>	

<b>Machine Id</b> :- 1132	<b>Serial No</b> :-
<b>Category</b> :- Gear Shapers CNC	<b>Model</b> :- LS154 ( CNC 6 AXIS )
<b>Country</b> :- Germany	<b>Make</b> :- Lorenz
<b>Type of Machine</b> :- CNC Gear Shaper 6 Axis	<b>Year</b> :-
<b>Weight</b> :- 0.0	<b>Dimensions</b> :-
<b>Power</b> :-	<b>Location</b> :- Mumbai Warehouse,India

Specification :-

CNC Gear Shaper 4 Axis with siemens 828 System,

Machine Mechanical Specifications:

Pitch rating depending on application	5 DP	Mod 5 mm
Maximum workpiece external diameter	6'	152 mm
Maximum workpiece internal diameter	11'	280 mm
Maximum tooth width (face width)	1.65'	42 mm
Maximum axial travel	2.56'	65 mm
Rapid travel - C (Cutter)	190'/min	4830 mm/min
D (Table)	380'/min	9660 mm/min
X	70'/min	1800 mm/min
Z	70'/min	1800 mm/min
Maximum X travel		175 mm
Minimum X travel		-30 mm
Maximum Z travel		65 mm
Minimum Z travel		0 mm
Stroking motor power	25 HP	18.5 kW
Stroking speed range, infinitely variable	100-1250 Strokes per minute	
Stroking Guide	Hydrostatic, Spur	

Machine Equipment List:

- Power Clamping
- Tailstock
- 4' Riser block
- Spring Leveling Wedges
- Servo controlled cutter elevation
- Cutter positioning
- Chip conveyor