KUNARK HITECH MACHINING & SALES PVT.LTD.

Kunark House, 269, Kunark Marg, Kaman Bhiwandi Road, Kaman,
Vasai Road (East),Dist: Thane -401208, Maharashtra,India.
Mobile&Whatsapp: +91 9867973046, Mobile 2:- +91 7977043901
Goggle Map:- https://maps.google.com/maps?q=19.372000+72.902095
Email: info@jkgears.com, dalbirbright@gmail.com website: www.jkgears.com

LIEBHERR
LIEBHERR WSC 251

LIEBHERR WSC 251

LIEBHERR WSC 251

LIEBHERR WSC 251

LIEBHERR
LIEBHERR WSC 251

LIEBHERR

LIEBHERR

LIEBHERR

LIEBHERR
LIEBHERR WSC 251

Video :--

please click here for video no. 01	
please click here for video no. 02	

please click here for video no. 03	
please click here for video no. 04	
please click here for video no. 05	
please click here for video no. 06	
please click here for video no. 07	
please click here for video no. 08	

Machine Id	***:-***	***1151***	**Serial No**	**:-**	
Category	**:-**	**Gear Related Machines**	**Model**	**:-**	**WSC 251**
Country	**:-**	**Germany**	**Make**	**:-**	**Liebherr**
Type of Machine	**:-**	**Six Axis CNC Gear Shaping Machine With Adjustable Taper 10 degree**	**Year**	**:-**	**1995**
Weight	**:-**	**0.0**	**Dimensions**	**:-**	
Power	**:-**		**Location**	**:-**	**Mumbai WareHouse, India**

Specification :-

Six AXis CNC Gear Shaper With 10 Degree Adjustable Facility (CNC B Axis).
Very Unique Machine with Extra Raiser block 200 mm.
SPUR Hydrostatic spindle guide.
Workpiece clamping hydraulic.

This machine is being offered in as is condition Old Orriginal Liebherr CNC System is Discarded. We can also offer it with an optional rebuild, recontrol or recertification. We Shall Carry Out The Following Process If You place order For Retroffting.All recontrolled and recertified machines are fully cleaned. All moving slides, spindles and parts handling systems are inspected for problems. Any gibs or adjustable backlash systems are adjusted to the best possible settings. All hydraulic, coolant, lubrication and pneumatic systems are checked for proper functionality and leaks. All filters are replaced. All worn hoses, broken cables, connectors, buttons, lamps and wires are replaced. All guarding is installed and checked. All machine cycles are tested. Parts are cut to verify the machine capability. Charts from the test cutting are documented for your viewing

Technical Data:

Max. Wheel Diameter: 250 mm
Gear Width: 80 mm
Max. Module: 6
Min. Module: 0.5
Max. distance between table and spindle-nose: 310 mm