

















<b>Machine Id</b>	<b>:- 1346</b>	<b>Serial No</b>	<b>:-</b>
<b>Category</b>	<b>:- Gear Hobbers</b>	<b>Model</b>	<b>:- PA320</b>
<b>Country</b>	<b>:- Germany</b>	<b>Make</b>	<b>:- Pfauter</b>
<b>Type of Machine</b>	<b>:- Gear Hobber Machine</b>	<b>Year</b>	<b>:-</b>
<b>Weight</b>	<b>:- 0.0</b>	<b>Dimensions</b>	<b>:-</b>
<b>Power</b>	<b>:-</b>	<b>Location</b>	<b>:- Mumbai Warehouse,India</b>

Specification :-

- Max. workpiece Ø350 mm**
- Max. modulus f. hobbing cutters 8 mm**
- Max. addendum circle Ø163 mm**
- L max. 230 mm (depending on cutter arbour Ø)**
- Cutter cutter Ø22, 27, 32, 40 mm**
- Mounting taper MK5**
- Radial carriage travel 225 mm**
- Tangential carriage travel 170 mm**
- Axial carriage travel 250 mm**
- Max. cutter head pivoting angle +30°...-40°**
- #workpiece spindle outside Ø350 mm**
- Workpiece spindle bore 150 mm**
- Counterholder travel 550 mm**
- Counterholder bore 150 mm**
- Speed - tool 120-400 rpm**
- Speed - tool spindle 1-40 rpm**
- Rapid speed on X axis 5,000 mm/min.**
- Rapid speed on Y axis 750 mm/min.**
- Rapid speed on Z axis 1,000 mm/min.**
- Autom. workpiece feeding unit**
- Cooling lubricant system**
- Oil mist extraction and filtering system**