## KUNARK HITECH MACHINING & SALES PVT.LTD.



Kunark House, 269, Kunark Marg, Kaman Bhiwandi Road, Kaman,
Vasai Road (East), Dist: Thane -401208, Maharashtra, India.
Mobile&Whatsapp: +91 9867973046, Mobile 2:- +91 7977043901

Goggle Map:- https://maps.google.com/maps?q=19.372000+72.902095

Email: info@jkgears.com, dalbirbright@gmail.com website: www.jkgears.com







Machine Id Serial No 440 :-**Gear Related Machines** Model 104 Category **United States** Make Country Gleason Type of Machine:-**Coniflex Straight Bevel Generator** Year Weight **Dimensions** :-0.0 :-Power Location Mumbai Warehouse,India

Specification :-

## 'Coniflex'

(1) Set-Up of Change Gears For Speed, Feed and Roll, Index and Ratio Roll Hydraulic Double-Acting Chucking Mechanism (Less Draw-in-Bar and Nut)

**Self-Contained Hydraulic System** 

**Self-Contained Coolant System** 

**Workhead Brake** 

**Full Guards Cover** 

**Full Compliment of Electrics (Motor/Controls)** 

## **SPECIFICATIONS:**

Cone Distance: 0 to 4-1/2'

Pitch Angle: 84 deg. 18 min. (max); 5 deg. 42 min. (min)

Extreme Ratio: 10-to-1

Pitch Diameter: 10-to-1 ratio; 8-1/2' (max)

Pitch Diameter: 1-to-1 ratio; 6' (max)

Diametral Pitch (coarsest): 3 DP

Diametral Pitch (finest): 20 DP

Face Width: 1-3/8' (max)

Index Range: 9 to 93 inclusive, and most numbers up to 175

Pressure Angles: 20, 22-1/2 &25 deg.

Diameter of Taper Hole at Large: 3-29/32'

Taper per Foot: 39/64'

Depth of Taper: 6'

Diameter of Hole Through: 2-7/16'

Spindle Nose to Machine Center: 1-1/2' to 9' Cutter Speeds: 98 to 286 (feet per minute)

Feeds: 4.2 to 69.2 (seconds per tooth)

Main Motor: 5 HP - 480V - 1800 RPM - 60 Hz - 3 PH