

# KUNARK HITECH MACHINING & SALES PVT.LTD.



Kunark House, 269, Kunark Marg, Kaman Bhiwandi Road, Kaman,

Vasai Road (East), Dist: Thane -401208, Maharashtra, India.

Mobile&Whatsapp: +91 9867973046, Mobile 2:- +91 7977043901

Goggle Map:- <https://maps.google.com/maps?q=19.372000+72.902095>

Email: [info@jkgears.com](mailto:info@jkgears.com), [dalbirbright@gmail.com](mailto:dalbirbright@gmail.com) website: [www.jkgears.com](http://www.jkgears.com)





Video :-

[please click here for video](#)



<b>Machine Id</b>	<b>:- 987</b>	<b>Serial No</b>	<b>:-</b>
<b>Category</b>	<b>:- Gear Related Machines</b>	<b>Model</b>	<b>:- 10-2</b>
<b>Country</b>	<b>:-</b>	<b>Make</b>	<b>:- FELLOWS</b>
<b>Type of Machine</b>	<b>:- CNC Gear Shaper with Tailstock</b>	<b>Year</b>	<b>:-</b>
<b>Weight</b>	<b>:- 0.0</b>	<b>Dimensions</b>	<b>:-</b>
<b>Power</b>	<b>:-</b>	<b>Location</b>	<b>:-</b>

Specification :-

**SPECIFICATIONS:**

**Inch Conversion**

**RETROFIT WITH SIEMSNS 808 2-AXIS CNC CONTROL**

**MAX PITCH DIAMETER, EXTERNAL 254 MM**

**MIN PITCH DIAMETER, INTERNAL 254 MM**

**MAX DIAMETRAL PITCH, SPUR 4 DP**

**MAX DIAMETRAL PITCH, HELICAL 5 DP**

**MAX FACE WIDTH 102 MM**

**MAX HELIX ANGLE W/ 127 MM CUTTER 45 DEG**

**MAX O D OF FIXTURE 483 MM**

**MAX STROKE LENGTH 127 MM**

**MAX STROKES PER MINUTE 800 SPM**

**DISTANCE - TABLETOP TO SPINDLE 203 MM**

**FEED PER STROKE .001-.040**

**CUTTER SPINDLE DIAMETER 90 MM**

**WORK SPINDLE BORE DIAMETER 149 MM**

**WORK SPINDLE BORE DEPTH 254 MM**

**TABLE SURFACE TO CUTTER SPINDLE UNDERSIDE**

**IN UPPERMOST POSITION 336 MM**

**WORKTABLE C L TO CUTTER SPINDLE CL 230 MM**

**MAXIMUM OD OF FIXTURE 483 MM**

**ROTARY FEED PER 25 MM OF STROKE .0254 MM-.3048 MM**

**ROTARY FEED FOR MULTI-PASS .001-.508 MM**

**RADIAL FEED RANGE PER STROKE .00254 MM-.508 MM**

**MAX RADIAL FEED PER MINUTE 3 MM**

**MACHINE DIMENSIONS 2362 MM X 2616 MM**

**MACHINE HEIGHT 2565 MM**

**APPROX MACHINE WEIGHT 5447 KG**

**EQUIPPED WITH:**

**HYDRAULICALLY OPERATED CUTTER GUARD ASSEMBLY**

**HYDRAULICALLY OPERATED COLLET FIXTURE**

Description :-

