

# KUNARK HITECH MACHINING & SALES PVT.LTD.



Kunark House, 269, Kunark Marg, Kaman Bhiwandi Road, Kaman,

Vasai Road (East), Dist: Thane -401208, Maharashtra, India.

Mobile: (+91) 9867973046 Factory: 0250-6454895

Email: [info@jkgears.com](mailto:info@jkgears.com), [dalbirbright@gmail.com](mailto:dalbirbright@gmail.com) website: [www.jkgears.com](http://www.jkgears.com)













<b>Machine Id</b>	<b>:- 1160</b>	<b>Serial No</b>	<b>:- 28222</b>
<b>Category</b>	<b>:- Gear Hobbers CNC</b>	<b>Model</b>	<b>:- PE150 Six Axis CNC Gear Hobber</b>
<b>Country</b>	<b>:- United States</b>	<b>Make</b>	<b>:- pfauter</b>
<b>Type of Machine</b>	<b>:- 6-Axis CNC Gear Hobber HIGH SPEED</b>	<b>Year</b>	<b>:- 0</b>
<b>Weight</b>	<b>:- 0.0</b>	<b>Dimensions</b>	<b>:-</b>
<b>Power</b>	<b>:-</b>	<b>Location</b>	<b>:- Mumbai Warehosue, India</b>

Specification :-  
Machine Under Power.

**This machine is being offered in as is condition. We can also offer it with a optional rebuild, recontrol or recertification. All recontrolled and recertified machines are fully cleaned. All moving slides, spindles and parts handling systems are inspected for problems. Any gibs or adjustable backlash systems are adjusted to the best possible settings. All hydraulic, coolant, lubrication and pneumatic systems are checked for proper functionality and leaks. All filters are replaced. All worn hoses, broken cables, connectors, buttons, lamps and wires are replaced. All guarding is installed and checked. All machine cycles are tested. Parts are cut to verify the machine capability. Charts from the test cutting are documented for your viewing.**

**Excellent 6 axis Fanuc 15m Gear Hobber**

**Machine under power**

**Maximum Workpiece Diameter:6'**

**Maximum Pitch (Module) In Steel With A Tensile**

**Strength Of Approx. 38 tons/sq. In.: D.P. 10**

**Maximum Axial Slide Travel: 6'**

**Minimum Center Distance Hob/Workpiece:4'**

**Maximum Center Distance Hob/Workpiece: 6'**

**Worktable Diameter: 6.29'**

**Index Worm Gear Diameter: 6.6'**

**Maximum Hob Head Swivel Angle:**

**- Standard: +/-45 Degrees**

**- Optional: + 30 Degrees/- 140 Degrees**

**Maximum Hob Diameter: 5'**

**Maximum Hob Length: 8.6'**

**Maximum Hob Shift: 6.7'**