KUNARK HITECH MACHINING & SALES PVT.LTD.



Kunark House, 269, Kunark Marg, Kaman Bhiwandi Road, Kaman, Vasai Road (East),Dist: Thane -401208, Maharashtra,India. Mobile:(+91) 9867973046 Factory:0250-6454895

Email: info@jkgears.com,dalbirbright@gmail.com website: www.jkgears.com













	PanelView 900
Alten-Bradley	
NET BEET	
	4

Machine Id	:-	1205	Serial No	:-	
Category	:-	Gear Chamfering Machine	Model	:-	SU SCT 3
Country	:-	Italy	Make	:-	Samputensili
Type of Machine	:-	Gear chamfering and deburring machines	Year	:-	
Weight	:-	0.0	Dimensions	:-	
Power	:-		Location	:-	Mumbai Warehouse,India

Specification :-

The SCT 3 Universal Chamfering and Deburring Machine with two tool heads has been designed for manufacturing spur and helical gears.

The SCT 3 features a shuttle feed loader for manual loading/unloading as standard and can be easily connected to a variety of automation systems or robots. The chamfering and deburring machine is a result of the technical collaboration between Samputensili Italy and Grind Master India in the field of advanced gear deburring and chamfering machines. Samputensili is a worldfamous global supplier of machine tools and cutting tools for the gear manufacturing.

Grind Master is well-known for its expertise in metal finishing, deburring and micro-finishing. Deburring operation using proven and reliable Samputensili deburring tool heads, spring-loaded to compensate for face width variations. Chamfering operation using the patented Samputensili chamfer and chamfer-roller tools for a better final result.

Self-centering tools guarantee symmetrical chamfers on both sides of the workpiece even in the instance of slight displacements between adjacent teeth (for example cluster gears). The two tool heads are meshed with the workpiece by pneumatic cylinders to compensate workpiece runout. This results in symmetrical and constant chamfers on all teeth.
Main advantages:
Chamfering, rolling and deburring in a single process
Easy connection to a variety of automation systems or robots
Possibility to use trademark tools in-house manufactured
Different faces are possible
Extreme short cycles time
Low cost for chamfering, rolling and deburring

Technical Data	
Model	SCT 3
Workpiece:	
Max. outside diameter	mm 25 –350
Max. workpiece length	mm 500 (750)
Max. toothed length	mm 200
Module range	mm 0,8 –8
Machine data:	
Number of tool heads	2
Max. outside diameter of tools	mm 200
Workpiece spindle speed range	rpm 0 -300